



SPOT DÉCO

In-Store Advertisement

Product	Layer	Thickness (micron)	Product code	Width (m)	Length (m)	Features	Release liner	Printability
WALL & GLASS graphics with Nano-Tack® Technology								
New! WALLY with Nano-Dots	transparent PET	140	WALLY-PETCG-13	1,37	50	designed for flat, clean and gloss surfaces (glasses, vehicles, screens, wall furniture, metals)	50 micron PET	E L U
	white PET	115	WALLY-PETWM-13				50 micron PET	
	Two Tack PET	65	TWOTACK-11	1,12	10	for fast placement of bifacial images	-	Not for printing (lamination only)
NANO-TACK Classic	transparent PET	155	NANO-PET1550-13	1,37	50	designed for flat, clean and gloss surfaces (glasses, vehicles, screens, wall furniture, metals)	50 micron PET	E L U
	white PP	175	NANO-PP1750-13				80 micron PET	
CLING & Static for Window Sign								
New! CLING STATIC Gloss soft vinyl	white gloss	180	CLING-W	1,07 - 1,37		for temporary applications of signage, pop notices, display and vehicle graphics	matt PET liner (75 my)	E L U
	clear gloss transparent	180	CLING-T	1,07 - 1,37				
Cling Tack High Clarity	ultra clear PVC, low tack, conformable & repositionable	80	HC-0830-12	1,27	30	designed for high clarity applications	matt PET liner (100 my)	E L U
IN-STORE Lighting								
TEXON	textile, white matt	190	TEXON-B19	1,07 - 1,37 - 1,60 3,10	30 50	for medium & big size light-boxes (with or without silicone edges)	-	E L U
FLOOR Graphics								
FLOOR Graphic Protection layer	professional antislip layer	200	FG-2050	1,06 - 1,27 - 1,52	50	for indoor shop centers	kraft paper (120gr)	Not for printing (lamination only)
New! FLOOR Graphics print & go	New! shop sign printable layer	160	RS-1630	1,07 - 1,27	30	INDOOR APPLICATIONS for shopping centers, fairs, stations, airports	kraft paper	E L U
	New! carpet floor printable layer	320	CF-3230-12	1,27	30	INDOOR APPLICATIONS for carpet-decoration during exhibitions and trade shows	PE kraft paper	E L U
	New! mak floor printable layer	550	MAK-5530-07	1,07	30	OUTDOOR APPLICATIONS for dividing lines and reserved areas	kraft paper	E L U
MAGNETIC Graphics System								
Ferro Film white PET	white matt	200	PET-FSV20	1,07 - 1,27 - 1,37 - 1,52	30	to be printed and applied on magnetic walls (multiple overlapping)	-	E L U
Magnet white PVC with adhesive	white matt with adhesive	600	MGSA-10260-WM	1,02	15	to install magnetic walls and display	Paper liner 120 gr	E U

Printability: **E** Eco-solvent **L** Designed for Latex, tested on HP 300/500/3000 series and Ricoh Pro L4100 series **E** Eco-Solvent, tests recommended
U UV curable **U** UV, tests recommended

